

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
12 June 2003 (12.06.2003)

PCT

(10) International Publication Number
WO 03/048503 A1

- (51) International Patent Classification⁷: **E21B 7/30**, 43/10, B21D 39/08
- (21) International Application Number: **PCT/GB02/05387**
- (22) International Filing Date:
29 November 2002 (29.11.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0128667.3 30 November 2001 (30.11.2001) GB
- (71) Applicant (for all designated States except US): **WEATHERFORD/LAMB, INC.** [US/US]; Suite 600, 515 Post Oak Boulevard, Houston, TX 77027 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **SIMPSON, Neil, Andrew, Abercrombie** [GB/GB]; Burn of Daff Farm, Downies, Portlethen, Aberdeen AB12 4QX (GB). **GRANT, David, H.** [GB/GB]; 1 Ness Circle, Ellon, Aberdeenshire AB41 9BU (GB). **STEPHENSON, David** [GB/AE]; A1 Moosa Tower 1, 20th Floor, P.O. Box 4627, Dubai (AE). **ADAMS, Grant** [GB/GB]; 4 Morningside Grove, Aberdeen AB10 7DJ (GB).
- (74) Agents: **MACDOUGALL, Donald, Carmichael et al.**; Cruikshank & Fairweather, 19 Royal Exchange Square, Glasgow G1 3AE (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: TUBING EXPANSION



(57) Abstract: A tubing expansion device (20) is adapted to be advanced axially, without rotation, through tubing (10) to be expanded. The device (20) comprises a body (22) and a plurality of expansion members (30, 32, 34) mounted on the body (22), the expansion members (30, 32, 34) being independently radially movable. The expansion members may be rotatable, or may be non-rotating.

WO 03/048503 A1

TUBING EXPANSION

FIELD OF THE INVENTION

This invention relates to a device for use in tubing expansion, and also to a method of expanding tubing. In particular, embodiments of the invention relate to devices and methods for use in expanding tubing downhole.

5 BACKGROUND OF THE INVENTION

In the oil and gas exploration and production industry, bores drilled to access subsurface hydrocarbon-bearing reservoirs are lined with tubing, known as casing and liner. Furthermore, strings of tubing may be located
10 within the cased bore to, for example, carry production fluid to surface. Recently, there have been numerous proposals to use tubing which is expanded downhole, that is tubing of a first diameter is run into a bore and then expanded to a larger second diameter downhole. This offers
15 many advantages to the operator, primarily providing the ability to create lined bores which do not necessarily suffer a loss in internal diameter each time a string of tubing is located in the bore, beyond an existing section of tubing-lined bore.

20 Early proposals for expanding tubing downhole featured the use of cones or mandrels, which are driven through the

tubing in order to expand the tubing. Other proposals include the use of roller expanders, which feature radially-urged rollers. The expanders are rotated within the tubing, and create a reduction in the wall thickness of the tubing, with a corresponding increase in diameter.

It is among the objectives of embodiments of the present invention to provide improved devices and methods for use in expanding tubing downhole.

SUMMARY OF THE INVENTION

According to a first aspect of the present invention there is provided a tubing expansion device, the device being adapted to be advanced axially through tubing to be expanded and comprising:

a body; and

a plurality of independently radially movable expansion members mounted on the body.

According to a further aspect of the present invention there is provided a method of expanding tubing, the method comprising the steps of:

providing an expansion device comprising a body and a plurality of independently radially movable expansion members mounted on the body;

moving the expansion device substantially axially through tubing to be expanded such that the expansion members are translated axially relative to the tubing; and

urging the expansion members radially outwards into contact with an inner wall of the tubing.

The provision of independently movable expansion members allows devices and methods in accordance with
5 embodiments of the invention to operate in situations where it is difficult or impossible to expand tubing to a uniformly cylindrical configuration, that is the device is "compliant". This is in contrast to the situation where an expansion cone or mandrel is utilised; if an area of the
10 tubing wall cannot be expanded to the cone diameter, the cone will be unable to pass, and may indeed become stuck fast in the tubing. Furthermore, the use of an axially movable expansion device avoids one of the difficulties associated with conventional rotary expansion systems,
15 which apply significant rotational torques to the tubing. In some cases, the torques may be sufficient to induce permanent rotational strain in the tubing, particularly in slotted tubing. The application of significant rotational torques to tubing strings undergoing expansion also has the
20 potential to create problems at threaded couplings between tubing sections.

Preferably, the expansion members are one or both of axially and circumferentially spaced.

Preferably, the expansion process is carried out
25 downhole. In this application the ability of the device to accommodate variations in tubing profile or diameter is

particularly useful, as it will often be the case that downhole tubing, whether in the form of casing or liner being expanded within a previously unlined or open bore, or a hanger or other tubing form being expanded within a larger diameter tubing, will encounter irregularities or restrictions that prevent expansion of the tubing to a constant diameter uniformly cylindrical configuration.

At least one of the plurality of expansion members may be radially movable relative to the body; the other of the expansion members may be radially fixed relative to the body. For example, three expansion members may be located at 120 degrees spacing on the body, and if one member is radially movable the device may still be capable of accommodating irregular expansion of the tubing. However, it is preferred that all of the expansion members are radially movable.

Preferably, at least one of the expansion members is rotatable, most preferably about an axis which lies substantially perpendicular to the tubing axis. Most preferably, a plurality of the expansion members are rotatable. This configuration of expansion member will tend to reduce the friction between the expansion members and the tubing inner wall, reducing the force necessary to move the device through the tubing and also reducing the rate of wear experienced by the expansion members. One or more of the expansion members may be non-rotating, and

provide for a predominantly sliding contact with the tubing wall. The faces of such members will typically be formed from a suitable wear-resistant material, such as a ceramic or a relatively hard metallic compound or alloy, and may be lubricated by well fluid or by fluid or material specifically provided for its lubrication properties.

In addition to the circumferentially spaced independently radially movable expansion members, further expansion members may be provided on the body which are collectively movable, that is the expansion members are not independently radially movable, or are non-compliant. Other expansion members may define a fixed diameter. Typically, any non-compliant or fixed diameter members will be located towards a leading end of the expander, and will be utilised to provide an initial degree of expansion.

The expansion members may be actuated by any appropriate means, including hydraulic actuation or mechanical actuation. In other embodiments the expansion members may be electrically actuated, or may be chemically or explosively actuated. Conveniently, the expansion members are mounted on pistons which are located in appropriate recesses or ports in the body, such that an elevated pressure within the body urges the piston, and thus the expansion member, radially outwardly. In other embodiments, axially movable pistons may be provided, which pistons act, via cams or the like, on radially movable keys

or fingers. Alternatively, the expansion members may be urged outwardly by springs or other biasing means, or the members themselves may be flexible or compliant or comprise flexible or compliant portions.

5 Preferably, the expansion device is provided in combination with driving means for applying an axial motive force to the body. The driving means may be located remotely of the body, for example where the invention is being utilised to expand tubing downhole, an arrangement
10 may be provided on surface for applying weight to a member on which the device is mounted. Alternatively, or in addition, the driving means may be arranged to engage the tubing in which the device is located. In some embodiments, the driving means may feature seals for
15 engaging the tubing inner surface, such that a fluid pressure differential across the seals creates an axial force on the device. The seals may be adapted for engaging the expanded tubing wall, particularly if the unexpanded tubing wall is non-cylindrical. However, it is preferred
20 that the seals are adapted for engaging the unexpanded tubing wall, as this is likely to be of a consistent form; the invention is primarily intended for use in situations where there is a possibility that the expanded tubing may include irregularities. The location of the seals on the
25 unexpanded tubing, that is in front of or below the device, also provides the numerous advantages as set out in our

earlier application WO02081863, the disclosure of which is incorporated herein by reference. Briefly, the elevated fluid pressure surrounding the device may be utilised to assist in expanding the tubing, and also serves to lubricate the device.

In other embodiments, the driving means may comprise a tractor of the like for pushing or pulling the device through the tubing.

In still further embodiments, the driving means may comprise an anchor or other gripping arrangement for engaging the tubing forwardly or rearwardly of the device, such that the device may then be pulled or pushed through the tubing relative to the fixed anchor. It is most preferred that such an anchor is provided forwardly of the device, such that the device is pulled through the tubing. This offers the advantage that the tubing form and dimensions at the anchor location are known, such that the anchor may be dimensioned appropriately, and it is more likely that the anchor will be securely and reliably located in the tubing.

The driving means may further comprise an arrangement to provide a hammer or impulse force to the device, or to vibrate the device. Downhole hammers and shock tools suitable for this purpose are known to those of skill in the art, and further arrangements are also disclosed in our earlier application no. GB0114872.5, the disclosure of

which is incorporated herein by reference.

Of course, the driving means may utilise any number of different arrangements, for example a combination of weight applied from surface and fluid pressure, or a combination of fluid pressure and mechanical force used to draw the device through tubing towards an anchor. Most preferably, the anchor is releasable.

The unexpanded tubing may take any appropriate form, and may have a cylindrical wall, a corrugated generally cylindrical wall, or the unexpanded tubing wall may be folded, such that the expansion process involves, at least in part, an unfolding of the wall. Thus the expansion of the tubing may involve one or both of circumferential extension of the wall and a re-configuration of the wall.

The tubing may be solid-walled, slotted or perforated, holed, partially holed, that is with areas of reduced wall thickness, or indeed may take any form. The tubing may comprise multiple elements, and may be in the form of a sand screen or the like.

The tubing will typically be metallic, but may be of any material or combination of materials appropriate to the circumstances.

The tubing may be formed of a plurality of tubing sections, or may be a substantially continuous length, for example a spoolable or reelable tubing.

The tubing may be located in open hole, or may be

located within a larger diameter tubing or bore. Typically, the tubing will be expanded into contact with the surrounding bore wall or larger diameter tubing.

These and other aspects of the present invention will now be described, by way of example, with reference to the accompanying drawings, in which:

Figure 1 is a diagrammatic illustration of expanded tubing;

Figure 2 is a perspective view of a tubing expansion device in accordance with a preferred embodiment of the present invention;

Figure 3 is a sectional view of Figure 2;

Figures 4 and 5 are part-cut away illustrations of tubing expansion devices in accordance with a further embodiment of the present invention; and

Figure 6 is a perspective view of a tubing expansion device in accordance with a still further embodiment of the present invention, shown in use.

Reference is first made to Figure 1 of the drawings, which illustrates a section of downhole tubing 10 which has been expanded by a tubing expansion device in accordance with an embodiment of the present invention, as will be described. The tubing 10 was originally of diameter d_1 . However, an expansion device has been run through the tubing 10, with the aim of expanding the tubing to a larger diameter d_2 . This expansion has brought the outer wall of

the tubing 10 into contact with the surrounding open bore wall. However, in one section of the tubing 10 a restriction 12 around the tubing has prevented the expansion of the tubing 10 to diameter d_2 , and the tubing
5 has only been expanded to a smaller diameter d_3 .

With many conventional expansion devices, such as expansion cones or mandrels, expansion of the tubing beyond the restriction 12 would not be possible, as the diameter of the cone is fixed and the cone would simply be unable to
10 expand the tubing and progress through the restriction 12. In practice, it is likely that the cone will become stuck at the restriction 12. However, as will be described, by utilising expansion devices in accordance with embodiments of the invention, it is possible to accommodate such
15 restrictions 12.

Reference will now also be made to Figures 2 and 3 of the drawings, which illustrate a tubing expansion device 20 in accordance with a preferred embodiment of the present invention. The device 20 comprises a generally cylindrical
20 tubular body 22 adapted for mounting to a support string (not shown). A bore 24 extends through the body 22 to allow fluid to be transmitted therethrough.

At least one roller is mounted in the body 22, and in the preferred illustrated embodiment there are five sets of
25 rollers, each roller with its axis of rotation perpendicular to the main axis of the body 22. Each set of

rollers has at least one roller, and in the preferred illustrated embodiment there are three angularly spaced rollers; in this embodiment the rollers are at 120° angular spacings, although other spacings may be adopted if
5 desired. The first and second sets of rollers 26, 28 may be radially fixed, that is the rollers 26, 28 describe a fixed radius. However, the rollers in each of the third, fourth, fifth and sixth sets 30, 32, 34, 36 may be radially movable. In particular, each roller may be mounted on a
10 piston 40 located within a respective radial body recess 42. Each recess 42 is in fluid communication with the body bore 24, such that an elevated fluid pressure within the bore 24 urges the rollers radially outwardly.

In use, the device 20 may be advanced through tubing
15 to be expanded by one of a number of means including application of weight from surface, or use of an anchor located ahead of the device 20, against which the device 20 is pulled through the tubing 10. The fixed radius rollers 26, 28 are dimensioned to describe a diameter slightly
20 larger than d_1 , such that the rollers 26, 28 will provide an initial degree of expansion of the tubing 10. Further expansion will be provided by the other sets of rollers 30, 32, 34, 36 which, when actuated, describe a larger, maximum diameter and are capable of expanding the tubing 10 to
25 diameter d_2 .

On encountering a restriction 12, which prevents the

tubing 10 from being expanded to diameter d_2 , the first and second sets of rollers 26, 28 will provide an initial relatively small degree of expansion which will not be affected by the restriction 12. However, on the other rollers 30, 32, 34, 36 encountering the restriction, the tubing 10 will be expanded to the maximum extent permitted by the restriction 12. The rollers 30, 32, 34, 36 will normally operate at their greatest radial extension, corresponding to diameter d_2 . However, where this is not possible, such as when prevented by the restriction 12, the rollers and their respective pistons will simply be forced radially inwardly relative to the body 22 by the tubing wall. Thus, the rollers 30, 32, 34 will expand the tubing 10 to the maximum extent permitted by the restriction and will still be able to pass through the resulting restriction in the expanded tubing diameter.

Figure 1 illustrates a restriction in the expanded tubing in the form of a necking of the tubing 10, however as each roller is mounted on a respective independently movable piston, the device 20 will also accommodate a restriction which occurs at only one portion of the circumference.

Reference is now made to Figures 4 and 5 of the drawings, which illustrate a tubing expansion device 50 in accordance with a further embodiment of the present invention. In this example, the device 50 features a

tubular body 52 carrying a leading fixed diameter swage 54 for inducing an initial degree of expansion, in a similar manner to the first and second roller sets 26, 28 described above. Following the fixed swage 54 are circumferentially spaced fingers 56. In this embodiment four fingers 56 are provided and are each mounted on a respective pivot pin 58, the axis of each pin 58 being perpendicular to the body axis. The fingers 56 are biased radially outward, and in normal circumstances will expand the tubing 10 to the diameter d_2 . However, on encountering a restriction 12, the fingers 56 may be forced inwardly, such that the device 50 extends the tubing to the intermediate diameter d_3 and may pass through and beyond the restriction 12.

Reference is now made to Figure 6 of the drawings, which illustrate a tubing expansion device 100 in accordance with a still further embodiment of the present invention. The device 100 is illustrated located within a section of liner 102 which the device is being used to expand, the illustrated section of liner 102 being located within a section of cemented casing 104; the device 100 is being utilised to create a liner hanger.

In this example, the device 100 features a central mandrel 106 carrying a leading sealing member in the form of a swab cup 108, and an expansion cone 110. The swab cup 108 is dimensioned to provide a sliding sealing contact with the inner surface of the liner 102, such that elevated

fluid pressure above the swab cup 108 tends to move the device 100 axially through the liner 102. Furthermore, the elevated fluid pressure also assists in the expansion of the liner 102, in combination with the mechanical expansion provided by the contact between the cone 110 and the liner 102.

The cone 110 is dimensioned and shaped to provide a diametric expansion of the liner 102 to a predetermined larger diameter as the cone 110 is forced through the liner 102. However, in contrast to conventional fixed diameter expansion cones, the cone 110 is at least semi-compliant, that is the cone 110 may be deformed or deflected to describe a slightly smaller diameter, or a non-circular form, in the event that the cone 110 encounters a restriction which prevents expansion of the liner 102 to the desired larger diameter cylindrical form. This is achieved by providing the cone 110 with a hollow annular body 112, and cutting the body 112 with angled slots 114 to define a number, in this example six, deflectable expansion members or fingers 116. Of course the fingers 116 are relatively stiff, to ensure a predictable degree of expansion, but may be deflected radially inwardly on encountering an immovable obstruction.

The slots 114 may be filled with a deformable material, typically an elastomer, or may be left free of material.

The device 100 may also include a leading fixed diameter swage (not shown) for inducing an initial degree of expansion, and furthermore serving to stabilise the cone 110.

5 It will be apparent to those of skill in the art that the above-described devices provide a convenient and effective means for expanding tubing downhole, and are particularly useful for applications where the ability to expand the tubing to a uniform cylindrical form cannot be
10 assured.

 Those of skill in the art will also recognise that these embodiments are merely exemplary of the present invention, and that various modifications and improvements may be made thereto, without departing from the scope of
15 the present invention.

CLAIMS:

1. A tubing expansion device adapted to be advanced axially through tubing to be expanded and comprising:
 - a body; and
 - 5 a plurality of expansion members mounted on the body, at least one of the expansion members being independently radially movable.
2. The device of claim 1, wherein the device is adapted to be advanced without rotation.
- 10 3. The device of claim 1 or 2, wherein the expansion members are configurable in an expansion configuration to describe a predetermined expansion diameter, said at least one of the expansion members is independently radially inwardly movable from the expansion configuration.
- 15 4. The device of claim 1, 2 or 3, wherein said at least one of the expansion members is adapted to be biased towards the expansion configuration.
5. The device of any of the preceding claims, wherein the expansion members are axially spaced.

6. The device of any of the preceding claims, wherein the expansion members are circumferentially spaced.

7. The device of any of the preceding claims, wherein the device is adapted for operation and location downhole in a drilled bore.

8. The device of any of the preceding claims, wherein at least two of the plurality of expansion members are independently radially movable relative to the body.

9. The device of claim 8, wherein said plurality of expansion members are radially movable relative to the body.

10. The device of any of the preceding claims, wherein at least one of the expansion members is rotatable.

11. The device of claim 10, wherein the body has a longitudinal axis and at least one of the expansion members is rotatable about an axis which lies substantially perpendicular to the body axis.

12. The device of claim 10 or 11, wherein a plurality of the expansion members are rotatable.

13. The device of any of claims 1 to 11, wherein at least one of the expansion members is non-rotating.

14. The device of any of the preceding claims, comprising further expansion members which are collectively radially
5 movable.

15. The device of claim 14, wherein said further expansion members are located towards a leading end of the device, for providing an initial degree of expansion.

16. The device of any of the preceding claims, comprising
10 at least one further expansion member which defines a fixed diameter.

17. The device of claim 16, wherein said at least one further expansion member is located towards a leading end of the device, for providing an initial degree of
15 expansion.

18. The device of any of the preceding claims, wherein said at least one expansion member is hydraulically actuated.

19. The device of claim 18, wherein said at least one
20 expansion member is mounted on a piston located in a recess

in the body, whereby an elevated pressure within the body urges the piston and the expansion member radially outwardly.

20. The device of any of claims 1 to 17, wherein said at
5 least one expansion member is mechanically actuated.

21. The device of any of the preceding claims, further comprising means for resiliently biasing said at least one expansion member radially outwardly.

22. The device of any of the preceding claims, further
10 comprising driving means for applying an axial motive force to the body.

23. The device of claim 22, wherein the driving means is arranged to engage tubing in which the device is located.

24. The device of claim 23, in which the driving means
15 comprises a seal member for engaging a tubing inner surface.

25. The device of claim 24, wherein the seal member is adapted for engaging expanded tubing wall.

26. The device of claim 24, wherein the seal member is

adapted for engaging unexpanded tubing wall.

27. The device of claim 23, wherein the driving means comprises a tractor for one of pushing and pulling the body through the tubing.

5 28. The device of claim 23, wherein the driving means comprises an anchor for engaging the tubing, such that the body may be one of pulled and pushed through the tubing relative to the fixed anchor.

10 29. The device of claim 28, wherein the anchor is provided forwards of the expansion member.

30. The device of claim 28 or 29, wherein the anchor is releasable.

15 31. The device of any of claims 22 to 30, wherein the driving means includes means for imparting an impulse force to the body.

32. The device of any of claims 22 to 31, wherein the driving means includes means for vibrating the body.

33. The device of any of the preceding claims, in combination with expandable tubing.

34. The device of claim 33, wherein the tubing is solid-walled.

35. The device of claim 33, wherein the tubing is slotted.

36. The device of claim 33, wherein the tubing is
5 perforated.

37. The device of any of claims 33 to 36, wherein the tubing comprises multiple elements.

38. The device of any of the preceding claims, further
10 comprising a seal member mounted on the body and adapted for engaging an inner wall of the tubing to be expanded.

39. A tubing expansion device adapted to be advanced axially through tubing to be expanded without rotation, the device comprising:

15 a body; and

a plurality of expansion members mounted on the body, the expansion members being configurable in an expansion configuration to describe an expansion diameter, at least one of the expansion members being independently radially
20 inwardly movable from the expansion configuration.

40. A tubing expansion device adapted to be advanced

axially through tubing to be expanded and comprising:

a body having a longitudinal axis; and

a plurality of expansion members mounted on the body,
at least one of the expansion members being independently

5 radially movable and at least one of the expansion members
being rotatable about an axis which lies substantially
perpendicular to the body axis.

41. A tubing expansion device adapted to be advanced
axially through tubing to be expanded and comprising:

10 a body; and

a plurality of expansion members mounted on the body,
at least one of the expansion members being independently
radially movable and at least one of the expansion members
being non-rotating.

15 42. A method of expanding tubing, the method comprising
the steps of:

providing an expansion device comprising a body and a
plurality of independently radially movable expansion
members mounted on the body;

20 moving the expansion device substantially axially
through tubing to be expanded; and

urging the expansion members radially outwards into
contact with an inner wall of the tubing.

43. The method of claim 42, comprising expanding the tubing to a form that is not uniformly cylindrical.

44. The method of claim 42 or 43, comprising expanding the tubing within a bore and into contact with an inner wall of the bore.

45. The method of claim 42, 43 or 44, comprising expanding the tubing in a subterranean bore.

46. The method of claim 42, 43, 44 or 45, comprising expanding the tubing within a bore that is not uniformly cylindrical.

47. The method of any of claims 44 to 46, comprising expanding the tubing within a bore that is of non-uniform diameter.

48. The method of any of claims 44 to 47, comprising expanding the tubing within a bore that has at least portions of non-circular section.

49. The method of any of claims 42 to 48, comprising varying the relative radial extension of the expansion members as the expansion members are translated axially relative to the tubing.

50. The method of any of claims 42 to 49, further comprising providing further expansion members which define a fixed diameter and expanding the tubing to an intermediate expanded diameter using said further expansion members.

51. The method of any of claims 42 to 50, comprising expanding the tubing within an unlined bore.

52. The method of any of claims 42 to 50, comprising expanding the tubing within a lined bore.

10 53. The method of any of claims 42 to 52, further comprising applying an impulse force to the body.

54. The method of any of claims 42 to 53, further comprising vibrating the body.

15 55. The method of any of claims 42 to 45, further comprising applying an elevated fluid pressure to the inner wall of the tubing.

56. A method of expanding tubing, the method comprising the steps of:

20 providing an expansion device comprising a body and a plurality of independently radially movable expansion

members mounted on the body;

locating the device in tubing to be expanded;

urging the expansion members radially outwards towards
an expansion configuration and into contact with an inner
5 wall of the tubing;

mounting at least one of the expansion members to
permit independent radially inward movement from the
expansion configuration; and

moving the expansion device substantially axially
10 through the tubing, without rotating the body.

1/4




Fig.1

2/4




Fig.2




Fig.3

3/4




Fig.4




Fig.5

4/4




Fig.6

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 02/05387

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 E21B7/30 E21B43/10 B21D39/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 E21B B21D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim.No.
X	WO 01 83932 A (TULLOCH RORY MCCRAE ;BAIN JAMES (GB); BBL DOWNHOLE TOOLS LTD (GB);) 8 November 2001 (2001-11-08) the whole document	1-9, 13-56
A	US 3 785 193 A (KINLEY M ET AL) 15 January 1974 (1974-01-15)	
A	US 5 014 779 A (ABDRAKHMANOV GABDRASHIT S ET AL) 14 May 1991 (1991-05-14)	
A	US 6 176 313 B1 (KENTER CORNELIS JAN ET AL) 23 January 2001 (2001-01-23)	
A	US 2001/020532 A1 (BENNETT ROD ET AL) 13 September 2001 (2001-09-13)	
	--- -/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the International filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

18 March 2003

Date of mailing of the international search report

26/03/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax (+31-70) 340-3016

Authorized officer

Peeters, L

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 02/05387

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>WO 01 46551 A (HARDING RICHARD PATRICK ;WEATHERFORD LAMB (US)) 28 June 2001 (2001-06-28)</p>	

INTERNATIONAL SEARCH REPORT

In International Application No

PCT/GB 02/05387

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0183932	A	08-11-2001	AU 4438001 A EP 1276953 A1 WO 0183932 A1 NO 20024901 A	12-11-2001 22-01-2003 08-11-2001 27-12-2002
US 3785193	A	15-01-1974	NONE	
US 5014779	A	14-05-1991	CA 1322151 A1 WO 9005831 A1 AU 621350 B2 AU 3189889 A DE 3887905 D1 EP 0397875 A1 NO 903219 A ,B, JP 3502351 T	14-09-1993 31-05-1990 12-03-1992 12-06-1990 24-03-1994 22-11-1990 18-07-1990 30-05-1991
US 6176313	B1	23-01-2001	AU 750116 B2 AU 5279999 A CA 2336353 A1 CN 1308705 T DE 69905164 D1 EA 2458 B1 WO 0001926 A1 EP 1092080 A1 NO 20006695 A	11-07-2002 24-01-2000 13-01-2000 15-08-2001 06-03-2003 25-04-2002 13-01-2000 18-04-2001 28-02-2001
US 2001020532	A1	13-09-2001	AU 3023000 A CA 2307538 A1 GB 2350137 A ,B GB 2359837 A ,B NO 20002585 A US 2002079101 A1	23-11-2000 20-11-2000 22-11-2000 05-09-2001 21-11-2000 27-06-2002
WO 0146551	A	28-06-2001	US 6325148 B1 AU 1044201 A EP 1242714 A1 WO 0146551 A1 NO 20022786 A US 2002185274 A1 US 2001045284 A1	04-12-2001 03-07-2001 25-09-2002 28-06-2001 14-08-2002 12-12-2002 29-11-2001

THIS PAGE BLANK (USPTO)